
AIRHANDLE WEIGHTLESS HANDLING







www.hofpartner.com/airhandle www.hofpartner.com/airhandle




www.hofpartner.com/airhandle www.hofpartner.com/airhandle www.hofpartner.com/airhandle



AIRHANDLE CRANE

AHC-80




AIRHANDLE AHC-80

Maximum load	80 Kg
Stroke	2000 mm
Arm length	3000 mm
Rotation	360°
Air supply	6 Bar
Electrical supplu	110-230 VAC



AIRHANDLE RAIL

AHR-60/40, FOR OVERHEAD RAILS




AIRHANDLE AHR-60/40

Maximum load	40/60 Kg
Stroke	1920/1600 mm
Air supply	6 Bar
Electrical supply	110-230 VAC



AIRHANDLE SINGLE CYLINDER

AHS-150 -8/-10/12, FOR OVERHEAD RAILS



AIRHANDLE AHS-150 -8/-10/12

Maximum load	150 Kg
Stroke	800/1000/1200 mm
Air supply	6 Bar
Electrical supply	110-230 VAC

FEATURES

All lifting functions and grippers are controlled by the electric control system. Several parameters can be adjusted to optimize different grippers and lifting situations. The AirHandle lift has as a standard all safety and functions needed for quick installment and safe and easy handling.

Safety

- AirHandle is set to correspond to gripper payload, which prevents lifting more than the maximum load.
- AirHandle prevents the load from being released in mid-air.
- AirHandle gives a feedback signal from the gripper when the load is safely gripped.

Functions

- Choose if you want the lift to be able to work in a counterbalanced lifting mode, lifting can then be done by moving the load itself without using the handle.
- You can adjust the handle's sensitivity, deadband and amplification of the AirHandle signal.
- Four different configurations possible, which you can change with a simple push of the button.












www.hofpartner.com/airhandle www.hofpartner.com/airhandle 15







Hofpartner AB Mor Annas väg 1 662 32 Åmål Sverige Tel. +46 (0)532 60 85 80 Mail info@hofpartner.se